

齿轮式气动马达参数表

Gear type pneumatic motor Technical parameter



型号 Model	工作压力 Mpa	功率 Power		转速 Speed		扭矩 Torque		耗气量 Air Consumption		旋转方向 ROTATION	重量 Weight		进气管口径 Input Hose (mm) Size
				自由速度 Free Speed	最大功率 时 At Max.HP	最大功率时扭矩 Max.Torque					立式 Vertical	卧式 Horizontal	
AMCX1.2	0.4	1	0.75	6500	3800	1.9	1.4	900	31.8	双向	4.5	5.7	12
	0.5	1.3	1	6700	3950	2.5	1.8	1200	42.4				
	0.6	1.6	1.2	7300	4000	2.8	2.1	1680	59.3				
	0.7	2	1.5	7500	4500	3.1	2.3	2100	74.2				
AMCX2	0.4	2.3	1.5	6000	3700	3.8	2.8	2160	76.3	双向	5.5	6.8	16
	0.5	2.8	1.8	6200	3850	4.4	3.2	2400	84.8				
	0.6	3.3	2	6400	3800	5	3.7	2880	101.7				
	0.7	3.7	2.2	6500	3900	5.3	3.9	3240	114.4				
AMCX3.5	0.4	3.3	2	5200	2700	7	5.2	3480	122.9	双向	18.5	18.5	20
	0.5	4	2.5	5650	2850	8.3	6.1	4200	148.3				
	0.6	4.6	3.5	5900	3100	11	8.1	4500	158.9				
	0.7	5.3	4.5	6100	3200	13.5	10	4720	166.7				
AMCX5	0.4	5.6	3.5	4600	2700	12.4	9.2	3780	133.5	双向	24	24	20
	0.5	6.3	4.5	4800	2900	14.8	10.9	4440	156.8				
	0.6	7.3	5	5400	3000	17.5	12.9	4980	175.9				
	0.7	7.7	5.5	5500	3100	20	14.8	5520	194.9				
AMCX7	0.4	2	4.5	3700	2500	17	12.5	3970	140.2	双向	45	45	35
	0.5	2.6	6.5	3900	2750	22.5	16.6	5220	184.3				
	0.6	9.3	7	4100	3100	24.6	18.2	5520	194.9				
	0.7	5.46	9	4200	3200	26.8	19.8	5880	207.6				
AMC9	0.4	12	5	3500	2620	18.5	13.7	3820	134.9	双向	65	65	40
	0.5	16.6	7	3700	2820	24	17.7	5350	188.9				
	0.6	21.3	9	3900	2900	30	22.1	5770	203.8				
	0.7	26	11	4000	3000	35	25.8	6600	233.1				
AMC16	0.4	12	9	3400	2250	39	28.8	4380	154.7	双向	80	80	45
	0.5	16.6	12.5	3700	2470	49	36.2	5880	207.6				
	0.63	21.3	16	3900	2600	59	43.5	7620	269.1				
	0.7	26	19.5	4050	2650	70.5	52	9000	317.8				

马达的型号表示 Motor model representation



齿轮式气动马达

Gear type pneumatic motor



AMCX3.5-IEC



AMCX5-IEC



AMC16



AMCX1.2-FG



AMCX2-RV



AMCX5-RF



AMCX2-IEC



AMCX1.2-RV



AMC9